




## Priming Spray

fast drying corrosion protector and paint primer for metal surfaces

- Once dry can be painted over with all common top coat paints.
- Ideally suited as a primer to cover PU and MS polymer sealing compounds.

	Colour	Contents ml	Art.No.	Pack Qty.
	light grey	400	<b>0890 180</b>	12/1



## Rust Converter

can be primed and painted over

- Penetrates rust on pre-cleaned surfaces.
- Turns iron oxide into a stable, insoluble, blue/black metalocene.
- Provides additional insulating and protecting effects.
- Not harmful to the environment.
- Sufficient for approx. 20m<sup>2</sup>.
- Can be stored over 1 year (in plastic containers, not exposed to full sun and temperatures over +40°C or to frost).

	Colour	Contents ml	Art.No.	Pack Qty.
	cream	1000	<b>0893 110</b>	12/1

### Instructions for Use

- Remove loose rust, paint, oil or wax layers by means of a wire brush.
- If necessary clean parts of salt deposits.
- Apply Rust Converter sparingly by brush, spray or roller.
- Application temperature (material and environment) 0°C to +40°C.
- Do not apply in full sun.
- Can be primed and painted over with all propriety paint and primer systems after 3 hours (reaction time).
- After application wash all appliances with clean water.